

file date: 2006/2/12  
print date: 2006/5/9  
file name: 08700.doc

1 {Kickplate (each leaf)}  
2 2 Stops  
3 Cylinder as required  
4

5 Specifier: Pair swinging same direction, not labeled, lockable (with storeroom function); select  
6 cylindrical (F86) or mortise (F07) function. To be used when doors are for equipment access  
7 only. Not to be used as means of exit.

8 HW-12: {NOT USED} Butts {Continuous gear hinge}  
9 Surface bolts (inactive leaf) {Flush bolts (inactive leaf)}  
10 Lockset {F86} {F07}  
11 2 Stops  
12 {Kickplate (each leaf)}  
13

14 Specifier: Pair, swinging same direction, labeled, not lockable. This is alternate to HW-8.

15 HW-13: {NOT USED} Butts {Continuous gear hinge}  
16 Closer {Corrosion resistant closer} (each leaf)  
17 Automatic flush bolts (inactive leaf)  
18 Coordinator  
19 Exit device 9847K{L}F BE  
20 *Exit device 9827K{L}F BE LBR*  
21 2 Stops  
22 {Kickplate (each leaf)}  
23

24 Specifier: Pair swinging same direction, lockable not labeled (with classroom function), with  
25 acoustical sound seals select cylindrical (F84) or mortise (F05) function.

26 HW-14: {NOT USED} Butts {Continuous gear hinge}  
27 Automatic flush bolts (inactive leaf)  
28 Coordinator  
29 Lockset {F84} {F05}  
30 Closer (each leaf) {Corrosion resistant closer (each leaf)}  
31 Automatic door bottom (each leaf)  
32 2 Stops  
33 {Kickplate(each leaf)}  
34 Sound seals  
35

36 HW-15: NOT USED.  
37

38 Specifier: Exterior door (with entrance or office-type function), lockable; select cylindrical (F81) or  
39 mortise (F13) function.

40 HW-16: ~~{NOT USED} Butts {Continuous gear hinge}~~  
41 ~~Closer {Corrosion resistant closer}~~  
42 ~~Lockset {F81} {F13}~~  
43 ~~{Kickplate}~~  
44

45 Specifier: Extremely corrosive chemical room door fire rated, lockable with panic device. Use for  
46 fluoride room (08) function.

47 HW-17: {NOT USED} Butts {Continuous gear hinge}  
48 Corrosion resistant closer  
49 Concealed overhead stop  
50 Exit device - 9875K{L}F  
51 Kickplate  
52 Cylinder  
53

file date: 2006/2/12  
print date: 2006/5/9  
file name: 08700.doc

1 Specifier: Exterior door, lockable with panic hardware. Substitute {L} if you want lever instead of  
2 knob.

3 HW-18: {NOT USED} Butts {Continuous gear hinge}  
4 Closer {Corrosion resistant closer}  
5 Exit device - 9875K {L}  
6 {Kickplate}  
7 Cylinder  
8

9 Specifier: Extremely corrosive interior chemical room pair of doors, fire rated, lockable, surface-  
10 mounted or concealed vertical rod panic device on each leaf. Use the optional text for surface-  
11 mounted panic device.

12 HW-19: {NOT USED} Butts {Continuous gear hinge}  
13 2 Corrosion resistant closers - Mount on pull side of door  
14 1 Exit device - 9847F - Less outside trim and cylinder (inactive leaf)  
15 1 Exit device - 9847K {L} F  
16 1 Exit device - 9827F LBR Less outside trim and cylinder (inactive  
17 leaf)  
18 1 Exit device - 9827K {L} F LBR  
19 Kickplate (each leaf)  
20 2 Stops  
21 {Concealed overhead stop each leaf}  
22 Cylinder  
23

24 Specifier: Pair exterior doors, lockable (with entrance or office-type function), select cylindrical  
25 (F81) or mortise (F13) function. If you don't want to use a coordinator and auto flush bolts, you  
26 could use hardware set #7.

27 HW-20: ~~{NOT USED}~~ Butts {Continuous gear hinge}  
28 Automatic flush bolts (inactive leaf)  
29 Coordinator  
30 Lockset ~~{F81}~~ {F13}  
31 Closer (each leaf) {Corrosion resistant closer (each leaf)}  
32 ~~{Kickplate (each leaf)}~~  
33

HW-20

34 HW-21: NOT USED.

35 HW-22: NOT USED.

38 Specifier: Pair exterior chlorine storage room doors (4 FT-0 x 12 FT-0 x 1-3/4 or 2-1/4 IN). Verify  
39 height and adjust doors accordingly. These doors cannot be used as an exit.

40 HW-23: {NOT USED} Butts {Continuous gear hinge}  
41 2 Chain Bolts - 6 IN with flat strike, with {9} FT-0 IN chain with  
42 {four} guides  
43 Surface Bolts (mounted at bottom of door)  
44 Dummy Trim - Inside and outside of each leaf  
45 2 Overhead Stops  
46 2 Door Holders {mount at {24} IN above bottom of door}  
47 {Kickplate (each leaf)}  
48

49 Specifier: Cylinder and optional weather stripping if using storefront type door: Add as required.

50 HW-24: {NOT USED} Cylinder: Type as required.  
51 Weatherstripping  
52

53 Specifier: Following is a pair of exterior doors swinging same direction with exit only function  
54 panic devices.